

READ BEFORE INSTALLING "NORDLOCK" WASHER PAIRS


The superior locking performance of a NordLock fastener is secured only if it is correctly assembled and the proper NordLock fastener combination is selected. It is important that the following instructions are closely observed:

NordLock Washer Pairs must be assembled cam face to cam face.


When used in conjunction with a bolt/nut fastener, install a pair of NordLock Washers, cam face to cam face, between both the bolt head and the nut and the joint material. The teeth of the washer pairs will bite into the bolt head and the joint material as well as the nut and the joint material on the corresponding side.

When used in conjunction with a cap screw or bolt in a threaded hole, install one pair of NordLock Washers, cam face to cam face, under the cap screw or bolt head.

The teeth of the washer pair will bite into the cap screw or bolt head on one side and the joint material on the other side.



INTERLOCKING CAMS



MADE IN SWEDEN

**FLEET
ENGINEERS**
INCORPORATED

1800 E. Keating Ave.
Muskegon, MI 49442
Ph. 800 333 7890
Fax 616 777 2720

INS-98008

PART NUMBER 993-01020			
Part No.	Size		Qty.
NL6	1/4"	6mm	50 pr
NL8	5/16"	8mm	40 pr
NL10	3/8"	10mm	25 pr
NL12	1/2"	12mm	20 pr
NL16	5/8"	16mm	20 pr